

## **EDGE FINDING**

## StudSensor™ L20

## Stud Finder with SpotLite® Pointer



The StudSensor™ L20 stud finder features a patented pinch grip design molded specifically to fit comfortably in the palm of your hand. The L20 displays an easy-to-understand user interface and SpotLite® Pointer which shines a bright arrow-shaped beam on the wall to clearly identify the edge of the target. Use to find the edges of studs to securely hang pictures and mirrors to the wall.

- StudScan mode locates the edges of wood or metal studs up to 3/4 in. (19 mm) deep
- · READY light indicates when calibration is complete and tool is ready for use
- . EDGE arrow illuminates when you have found the edge of the stud
- · Zircon's patented "over-the-stud" indication alerts you to start the scan in a new location if scanning begins over
- . SpotLite® Pointer shines an arrow-shaped light on the wall to clearly indicate the edge of the stud
- . "V" marker groove for more accurate marking of stud edge location





## **SPECIFICATIONS**

Dimensions 5.33 in. H x 2.14 in. W x 1.36 in. D

(135 mm x 54 mm x 35 mm)

Weight 2.0 oz. (57 g) without battery

**Battery Type** 9V alkaline, required

Position Accuracy\*

Wood studs: Typically within 1/8 in. (3 mm) using the dual scan and mark procedure

Metal studs: Typically within ½ in. (13 mm) using the dual scan and mark procedure

Depth\* Typically up to 3/4 in. (19 mm)

**Operating Temperature** 

20° to 105°F (-7° to 41°C)

Storage Temperature

-20° to 150°F (-29° to 66°C)

Humidity 5-90% RH (non-condensing)

Water Resistance

Splash and water resistant, not waterproof

\*NOTE: Sensing depth and accuracy can vary due to moisture, content of materials, wall texture, paint, etc. Not recommended for use on lath and plaster. Indoor use only.









© 2017. SpotLite, StudSensor, and Zircon are trademarks or registered trademarks of Zircon Corporation • C/N 2245 Rev C 03/17