

# EXITPOINT® XL500

## Through-Hole Drill Guide



Accurately locate exit points through floors, walls, ceilings, and more with magnetic field detection technology.

The new Zircon® ExitPoint® XL500 through-hole drill guide provides a fast and easy solution to determine the exit point location for your drilling and coring applications. Locate a precise spot, without measuring, before you start your project to save time and money by eliminating guesswork, rework, and needless holes. Scans through most types of non-metallic building materials such as wood, drywall, gypsum panels, bricks, and poured concrete up to 9 in. (22.9 cm) thick.

Ideal for cable and wire installations, concrete scanning, and any time through-hole drilling is required. Simply affix the Target Magnet on the spot you want to drill, then scan in the same vicinity on the opposite surface of the Target Magnet with the Receiver. The Directional Indicator LEDs will point toward the magnet. When the Receiver is near the Target Magnet, all LEDs will light red to indicate the drill location.

Features two scan modes:

- **Normal Mode** scans through conventional interior walls up to 4.5 in. (11.4 cm) thick
- **DeepScan® Mode** scans through materials up to 9 in. (22.9 cm) thick

Includes Receiver, (1) small and (1) large Target Magnet, (9) reusable adhesive disks, 9V battery, and protective carrying case.



- Drill Guide
- DeepScan® Mode

### Specifications

**Dimensions** 9.1 in. x 4.8 in. x 1.9 in.  
(23.2 cm x 12.2 cm x 4.8 cm)

**Weight** 7.4 oz (210 g) with battery

**Battery Type**  
9V alkaline battery required, included

**Position Accuracy**  
Typically within ½ in. (1.3 cm)

**Depth\*** **Normal mode** up to 4.5 in. (11.4 cm)  
**DeepScan®** up to 9 in. (22.9 cm)

**Operating Temperature**  
20° to 105°F (-7° to 41°C)

**Storage Temperature**  
-20° to 105°F (29° to 66°C)

**Humidity** 5-90% (non-condensing)

**Water Resistance**  
Splash and water resistant, not waterproof

**\*NOTE: USE ONLY IN ACCORDANCE WITH EXITPOINT® XL500 INSTRUCTIONS.**  
Specifications subject to change. Sensing depth and accuracy can vary. Does not detect hidden objects. Must use other information sources to locate, and avoid, objects behind surface before drilling.